WINNER-T 6T Configuration Table

Electrical System	Electronic Control System	Enpower Fully Intelligent Controller		
	Battery	2V 250Ah (36 units) 72V High-Capacity Deep-Cycle Flooded Lead-Acid Batteries (Special for Tractors)		
	Motor	11.5KW AC Motor (Special for Tractors)		
	Charger	Intelligent Onboard Charger with Automatic Power-Off When Fully Charged		
Technical Specifications	Charging Time	8-10 Hours (at 80% Depth of Discharge)		
	Charging Input Voltage	220V		
	Length × Width × Height	2300×1200×2000mm	Braking Distance	≤5m
	Curb Weight	1050kg	Rated Passenger Capacity	1
	Maximum Towing Capacity	2000-3000kg	Maximum Travel Speed	28km/h
	Front/Rear Track	960/960mm	Maximum Gradeability	10%
	Wheelbase	1800mm	Minimum Turning Radius	3.5m
	Minimum Ground Clearance	130mm	Driving Range	80-100km
Body System	Seats	Seat (Single Seat, Leather + High-Resilience PU)		
	Body	Steel Frame + Sheet Metal Body		
	Instrument Panel	LCD Instrument Display (Voltage, Current, Speed, Mileage, Lighting, F/R Direction Signals)		
	Rearview Mirrors	Adjustable Manual Wide-View Exterior Rearview Mirrors		
	Lighting and Signals	LED Headlights, Turn Signals, Combined Taillights, Brake Lights, Electric Horn + Reverse Buzzer		
	Switches	Ignition Switch, F/R Gear Switch		
	Frame	Steel Frame		
	Doors	Sheet Metal Doors ×2		
	Steering Wheel	Polyurethane Foam Steering Wheel		
Chassis System	Powertrain System	Continuously Variable Transmission (CVT) System		
	Steering System	Rack and Pinion Steering + Electronic Power Steering		
	Front Axle and Suspension	Integrated Front Axle		
	Rear Axle and Suspension	Integrated Rear Axle (18.12:1) + High-Strength Leaf Springs + Hydraulic Shock Absorbers		
	Braking System	Drum Hydraulic Brakes, Dual-Circuit Braking System, Parking Brake, Brake Booster		
	Wheels	Front Wheels: 500-8 Rear Wheels: 650-10 Hubs		

Winner Electric Power Energy Company