## WINNER-TT 5T Configuration Table

Electrical System	Electronic Control System	96V Fully Intelligent Controller   Brand: Enpower		
	Battery	96V 200Ah Lithium Battery (3-year warranty)		
	Motor	11.5KW Three-Phase Asynchronous AC  Motor   With regenerative braking function		
	Charger	Aviation Aluminum Intelligent On-board Charger   Auto power-off when fully charged		
	Charging Time	Charging Time: 8-10 hours (at 80% discharge rate)		
Technical	Charging Input Voltage	220V		
	Length × Width × Height (mm)	3700*1450*2100	Braking Distance	≤5.5m
l Specifications	Cargo Compartment Dimensions (mm)	2200*1450*350	Rated Passenger Capacity	2
cifi	Payload Payload	5000kg	Maximum Travel Speed	28km/h
cat	Front/Rear Track	1235/1235mm	Maximum Gradeability	15%
ions	Wheelbase	1940mm	Minimum Turning Radius	5.5m
01	Minimum Ground Clearance	150mm	Driving Range	80-100
Body System	Seats	Premium faux leather seats (1+1 configuration, leather + high-resilience PU, beige seats)		
	Body	Carbon steel frame (Q235) / Sheet metal body / ABS engineering plastic molded dashboard		
	Instrument Panel	LCD instrument display (showing voltage, current, speed, mileage, lighting, forward/reverse signals, etc.)		
	Rearview Mirror	Wide-view adjustable manual exterior rearview mirrors		
	Lighting & Signals	High-brightness LED headlights, turn signals, combined taillights, brake lights, electric horn, and reverse buzzer		
еш	Audio System	Premium car audio with MP3 player, professional speakers, and USB port		
	Switches	Ignition switch, combined light/wiper switch, forward/reverse switch		
	Doors	Removable carbon steel doors (Q235) with built-in tempered glass sliding windows		
	Frame	Welded carbon steel frame (Q235) / Anti-rust paint treatment		
	Steering Wheel	Polyurethane foam steering wheel		
	Powertrain System	Continuously Variable Transmission (CVT) system		
Ch	Steering System	Worm-and-sector steering (automatic clearance compensation) + EPS power steering		
Chassia System	Front Axle & Suspension	Integrated load-bearing front axle		
	Rear Axle &	Integrated rear axle (18.12:1) with aviation aluminum differential assembly		
	Suspension	+ high-strength leaf springs + tubular hydraulic shock absorbers		
	Braking System	Drum hydraulic brakes, dual-circuit braking, parking brake system		
	Wheels	650-10 industrial tires		

Air conditioning	conditioning Roof-mounted cooling and heating air conditioning system in cabin	
Warranty	1-year vehicle warranty + lifetime technical support	

Minner Electric Poller Energy Company